



TECHNICAL DATA:

1. RATED VOLTAGE: DC12V
2. PULL CURRENT: 50AMP AT .7 SEC.
3. HOLD CURRENT: 1AMP
4. STROKE: 1"
5. PULL RATING: 50N
(SPRING FORCE 20.5N)
6. HOLDING RATE: 160N
(SPRING FORCE 40N)
7. WORKING TEMP: -40°C TO 120°C
8. UNIVERSAL JOINT ANGLE: >30°
9. HOUSING OF SOLENOID AND CONTROL MODULES MUST BE FIRMLY GROUNDED

REL	M.B.	11-18-09	RELEASED	REV	BY	DATE	DESCRIPTION	SCALE	DRAW	DATE	CHECKED	APPROVED	DRAWING NO.	IMPLIED TOLERANCE
														XX
														XXX
														XXXX
														FRACTIONAL
														ANGULAR
														85 deg

TITLE												
ACTUATOR, THROTTLE PULL ASSEMBLY												
CAD DRAWING DO NOT REVISE MANUALLY												
1A-002-2-A-1												

THIS DRAWING IS THE PROPERTY OF AIR-TECH INC. AND ALL THE INFORMATION THEREON IS CONFIDENTIAL AND MUST NOT BE MADE PUBLIC, NOR COPIED, NOR USED TO THE DISADVANTAGE OF AIR-TECH INC. AND IS SUBJECT TO RETURN ON DEMAND.