

VC-144

RADIO RECEIVER

Our VC-144 receiver is the flagship wireless control platform in our lineup. It's loaded down with I/O count and options, and can run any of our radios at any frequency. It's a processing powerhouse for demanding applications with its high-powered DSP processor, and up to 37 pins available for I/O and data. It's able to accept and provide almost any signal type common in the mobile industry. In addition, it's got WiFi, RS-232, and dual CAN available (normally via SAE-J1939). We handle all of this in a module that's only 5.76"x6", highly environmentally hardened, fully solid-state, and 100% US-made (down to the board level) in our facility.



PHYSICAL

Weight	1.0 lb.	Ingress Protection	IP66
Operating Temperature	-40° to +85° C	Housing Material	Glass-filled polymer
Storage Temperature	-55° to +85° C	Certification	FCC, IC, C-Tick, others on request

I/O:

Protocols	RS-232, CANbus (2x): SAE-J1939, RF: 900MHz FHSS or 2.4GHZ DSSS, WiFi	
Supply Voltage	12V/24V nominal (9V – 30VDC)	
Analog Inputs	18 Maximum, 0-32VDC (other ranges available), 12-bit resolution with on-board 5V Reference supply available for sensors. Inputs are protected from overvoltage & transient spikes.	
Digital Inputs	18 Maximum	
Frequency Inputs	1 Maximum	12/24V nominal input range with protection for overvoltage/transient spike
Quadrature Inputs	None	
PWM Outputs	14 Maximum (12CR), 5A max, sourcing	
Digital Outputs	30 Maximum	
Variable Voltage Outputs	12 Maximum, 0-30V (other ranges available)	

***These are maximums only. Using all the inputs or outputs of one type may limit other I/O. Please contact us for no-charge application support.**

WIRELESS:

Frequency	900MHz FHSS, 2.4GHz DSSS. With powers up to 100mW
Operating Range	300ft, 1000ft, or Half Mile (nominal)

